

www.neogroup.eu

Industrijos St. 2, LT-95346 Rimkai Dovilai Eldership, Klaipėda District, Lithuania Phone +370 46 466710 Fax +370 46 466711 E-mail info@neogroup.eu

# PRODUCT TECHNICAL DATA SHEET

Rev.06. 2017/09/18



### **General information**

### **Product Description**

Neopolyol 260 P is a premium quality Aromatic Polyester Polyol based on phthalic anhydride. This product characterized by balanced hydroxyl number and viscosity. Does not contain stabilizers or flame retardant additives. It is used to improve mechanical and fire performance of low and medium isocyanate index rigid foams.

## **Application**

- ♦ Rigid Polyurethane (PU) Foam
- Polyisocyanurate (PIR) Foam
- ♦ One Component Foam

### **Product Characteristics**

Property	Value	Test method
Hydroxyl Number, mg KOH/g	250÷280	DIN 53240
Acid Number, mg KOH/g	≤ 2.0	DIN 53402
Dynamic Viscosity (25°C), mPa·s	2500÷5500	ASTM D 4878-08
Water content, wt.%	≤ 0.1	WN-B010-1065 D
Density, g/cm <sup>3</sup>	1.2÷1.3	ASTM D 4669-07
Appearance	liquid	ASTM D 4669-07

### Storage and handling

Product has a shelf life of 6 month, in tightly closed drums or containers. Recommended storage conditions are 25÷60°C.

